



Moving the Nation's Grain...



Our frames are designed with strength and quality.

Made to last!



Sealed drive shaft bearings



Electric motor mounts in place for easy transition



Heavy duty clevis hitch with easy 2-pin removal for hopper attachment



Long service life greasable, lower intake bushing assembly



Deluxe rims with **new** 13" Highway rated tires



High-quality brake winch lowers and raises the auger




Top drive chain cover and lubrication housing features double-tapered bearings

## Other Features:

- Powder Coat Plus<sup>TM</sup>
- Iron Edge Plus<sup>TM</sup> Flighting Up to 50% thicker than regular flighting throughout entire auger
- Tapered bearing gearbox
- Ge<mark>arbox can be mounted for PTO on either side of auger</mark>

## **General Specifications**

Model	(A) Raised Height	(B) Transport Height (TOP)	Width	(C) Lowered Reach	(D) Raised Reach	Tire Size	
T 1032	19' 5"	9' 9"	74"	10' 8"	7' 4"	13"	
T 1042	25' 7"	12' 9"	86"	16' 4"	11 ' 2"	13"	
T 1052	32' 7"	14' (HITCH ON GROUND)	112"	21' <i>7</i> "	11' 10"	15"	



## HARVEST INTERNATIONAL, INC.

1130 Riverview Drive Cherokee, Iowa 51012 USA 888.218.5373 • 712.225.6313 • Fax 712.225.2336 www.harvestauger.com Dealer: